

09727718-113000




Figure 1

The circuit diagram shows a differential amplifier with a resistor network. The input stage consists of two NMOS transistors, Q1 and Q2, whose sources are connected to a common source node. This node is connected to a PMOS transistor Q3, which is biased by a current source (represented by a battery symbol) and a resistor R7. The gates of Q1 and Q2 are connected to a common gate node, which is biased by a current source and a resistor R8. The gates of Q1 and Q2 are also connected to a resistor network consisting of resistors R1, R2, R3, and R4. The output of the amplifier is taken from the drain of Q2, which is connected to a resistor R5 and a load resistor R6. The output voltage is labeled Vout. The circuit is powered by a positive supply +V and a negative supply -V. A handwritten label '22' with an arrow points to the circuit.

← 22




Figure 3




Figure 4

The diagram shows a central vertical rectangular unit labeled 330. At the bottom of this unit is a horizontal array of vertical bars, labeled 36. Two circular sensors are positioned above the central unit. The sensor on the left has a dashed arrow pointing from the central unit towards it, and its needle points straight up. The sensor on the right has a solid arrow pointing from the central unit towards it, and its needle points towards the upper right.

Figure 5

09727718-113000




Figure 6

Figure 7

09727748.1.3000




Figure 8






Figure 9

730

38

136

Figure 10

09727718.113000




Figure 11